AVerVision M70

Interactive Visualizer

- 12X optical zoom
- Onboard annotation
- 30fps recording to SDHC/OTG
- Full HD 1080p output resolution
- HDMI support

Product Specifications & Features

Image / Video	
Image Sensor	1/3.2" CMOS Color Image Sensor
Total Pixels	5M Pixels
Output Resolution	Full HD1080p (1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768)
TV Line	700
Zoom	192X Total Zoom (24X AVer® Optical Zoom* + 8X Digital Zoom)
Frame Rate	30fps (Max.)
Focus	Auto / Manual
Shooting Area	A3 Landscape (372 x 279 mm Max.)

Functions	
Image Rotation	Electronic Rotation 0° / 90° / 180° / 270°
Internal Storage	Built-in Memory (Max: 80 images @ 5M; 240 images @ XGA)
External Storage	SDHC Card (32GB Max.) / USB Flash Drive (64GB Max.)
Recording	Yes (30fps to SDHC Card or USB Flash Drive)
Onboard Annotation	Yes (no software is needed)
Image Effects	Color / B&W / Negative
Image Adjustments (White Balance / Exposure)	Auto / Manual
Presentation Tools	Yes (Spotlight & Visor)
Split Screen	Yes (Vertical & Horizontal)
Picture-in-Picture	Yes
Display Mode	Sharp / Graphic / Motion / Microscope / Macro / Infinite
Capture Mode	Single / Continuous
User Profiles	Up to 3
Timer	Yes
Flicker Filter Control	Yes (50/60Hz)
Remote Control	Yes
Light Source	Embedded LED Lamp

* 24X AVer® Optical Zoom (12X Optical Zoom + 2X AVerZoom™)

Connectivity	
HDMI Output	Yes
RGB I/O	1 In; 1 Out (15-Pins D-Sub, Pass Through)
Composite Video Output	Yes (NTSC or PAL)
RS-232 Port	Yes (with S-Video / RS-232 Adapter cable)
Mini USB 2.0 Port	Yes (PC Camera / Built-in Image Download)
USB 2.0 Port	Yes (A Type)
Audio Input	MIC In (3.5mm Jack, Pink)
Audio Output	Audio Out (3.5mm Jack, Green)

Others	
Dimensions (W x H x D)	Operating: 182 x 504 x 452 mm Folded: x 182 x 63 x 367 mm
Net Weight	2.1kg (4.63lbs)
Power Source	AC 100V~240V, 50/60 Hz
Power Consumption	16.8 Watt with LED lamp OFF 18.0 Watt with LED lamp ON <0.5 Watt in stand-by mode
Certifications	FCC, CE

Package Content

AVerVision M70 Unit	Mini USB Cable	Quick Guide
Remote Control with Batteries	Power Adapter (12V, 2A)	Anti-Glare Sheet
RCA Cable	A+ Interactive Software CD	Warranty Card
RGB Cable	User Manual CD	Carrying Bag
Composite / RS-232 Y Cable		

All-New A+ Interactive Software 2

A+ Interactive Software 2 offers a brand new user interface that allows you to draw and make notes on top of images, record video and audio, set up a multiple-user network, and much more.

System Requirements

Windows® XP, Vista and 7

☐ Intel® Pentium IV 3 GHz or Intel® Core 2 Duo or better (recommended)

☐ 1 GB of RAM (2 GB recommended)

☐ 100 MB free hard disk space for basic installation (without content in Gallery)

Maahantuonti ja markkinointi: EP-Engineering Oy MediaSolution, PL115, 01801 KLAUKKALA, P.09-879 5639 FAX 09-879 5448, www.mediasolution.fi