


# AMC-E Series IP+SDI HD PTZ Camera



## Features

- H.265 video compression, dual stream;
- Compatible with ONVIF, RTSP, RTMP protocols;
- Up to 20x optical zoom, 12x digital zoom, 72.5° FOV;
- With OSD menu, support image flip;
- Come with IR remote controller;
- Support standard VISCA & Pelco communication protocols;
- RS232IN/IR & RS232OUT/RS485 control interface, support daisy chain;
- Special mechanical PTZ driving system, ensure precise positioning.

## Dimensions



## Technical Data

Model	AMC-E200N	AMC-E220N
Image Sensor	1/2.8" Exmor CMOS, 2.14MP	
Resolution	1080p/60, 1080p/30, 1080i/60, 720p/60, 720p/30 1080p/50, 1080p/25, 1080i/50, 720p/50, 720p/25	
Focal	3.9mm - 46.8mm	f=4.7mm - 94.0mm
Iris	F1.6 - F2.8	F1.6 - F3.5
Optical Zoom	12X	20X
Digital Zoom	12X	12X
Field of View	72.5° - 6.3°	59.5° - 2.9°
Focus	Auto, Manual, PTZ Trigger AF, One Push	
Minimum Illumination	0.5Lux (Color), 0.1Lux (B/W)	
Shutter Speed	1/1 ~ 1/10,000s	
AGC	Auto / Manual	
White Balance	Auto, Indoor, Outdoor, One Push, Manual, Automatic Tracking	
AE Control	Auto, Manual, Shutter Priority, Iris Priority, Intelligence	
<b>Pan &amp; Tilt</b>		
Pan Range	-170° ~ +170°	
Tilt Range	-30° ~ +90°	
Pan Speed	0.1° ~ 120°/s	
Tilt Speed	0.1° ~ 80°/s	
Preset Number	256	
OSD	Yes	
Image Flip	Yes	
<b>Network</b>		
Max. Image Size	1920 x 1080@60fps	
Video Compression	H.265, H.264	
Audio Compression	AAC	
Protocol	HTTP / RTSP / RTMP / RTP / TCP / UDP / ONVIF	
Dual Stream	Support	
Simultaneous Users	Up to 10 users	
<b>Interface</b>		
Video Output(HD)	DVI-D, HD-SDI	
Control Interface	RS-232IN/IR, RS-232OUT/RS-485	
Ethernet	RJ45, 100M	
<b>General</b>		
Control Protocol	VISCA and Support Daisy Chain, PELCO-D, PELCO-P	
Address	0~63	
Power Supply	DC12V	
Working Temperature	0°C~ +40°C	
Storage Temperature	-20°C~ +60°C	
Dimension	243mm x 145mm x 163mm	
Weight	1.2KG	
Body Color	Grey	

## Accessories

