

UHV USB 3.0/HDMI/LAN WEB-Camera UHV-300-U3



Features

- ※ Superb High-definition Image: 1/2.5" inch high quality CMOS sensor. Resolution is up to 4K with frame rate up to 30fps
- ※ Wide FOV: 83° large wide angle and small distortion lens: 3x zoom lens
- ※ Advanced Focusing Technique : VCM motor auto-focusing lens, advanced auto-focusing algorithm makes the camera auto focusing rapidly, accurately and stably. ※ Low Noise and High SNR: low Noise CMOS effectively ensure high SNR of camera video ※ Multiple Video Output Interfaces: Support HDMI, USB3.0 and LAN.
- ※ Multiple Audio Video Compression: Support H.265/H.264/MJPEG video compression; supports AAC, MP3, PCM audio compression; support up to 3840x2160 resolution 30fps compression
- ※ Stereo sound: Built-in pickup to present clear stereo sound, no external device required
- ※ POE: LAN interface supports POE function
- ※ Built-in Pickup: two built-in MIC pickups
- ※ Multiple Installation: Standard equipped with mold clamp, easy to install on any devices, such as LCD screen, laptop, table and tripod
- ※ Easy to Use: No need to download driver, USB output interface, plug and play
- ※ Wide Application: personal video conferencing, enterprise video conferencing, collaboration meeting etc.

Dimension(mm)

Technical Specification

Model No.	UHV-300-U3
Camera Parameter	
Image Sensor	1/2.5" inch High Quality 4K CMOS sensor
Effective Pixels	8.28MP 16:9
Video Format	HDMI Video Output Format: 1080p30/25/29.97; 1080i60/50/59.94; 720p30/25/29.97 USB 3.0 Video Output Format: up to 3840x2160p30
Digital Zoom	3X
www.winsafecctv.com	
View Angle	93.5°/83°/53.1°
Min. Illumination	0.5Lux(F1.8, AGC ON)
Lens	3.5mm
Aperture	2.0+5%
DNR	2D & 3D DNR
White Balance	Auto/Manual/One Push/3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K/7000K
Focus	Auto/Manual/One Push
Exposure	Auto/Manual
Backlight contrast	ON / OFF
SNR	Above 50dB
Video Interfaces	
	USB3.0, HDMI, LAN(POE)
Video Compression Format	
	MJPEG, H.264, H.265
Audio Input Interface	
	Built in high sensitive digital pickup

Other Parameter	
Input Voltage	DC5V
Input Current	1A (Max.)
Power Consumption	5W (Max.)
Store Temperature, Humidity	- 10°C - +60°C, 20% - 95%
Working Temperature, Humidity	-10°C - +50°C, 20% - 80%
Dimension(WxHxD)	220mm x 92.75mm x 56mm
Application	Indoor