

AMC Speaker Tracking Camera AMC-G200T






AMC-G200T speaker tracking camera helps to achieve intelligent meeting experience, implemented with both audio positioning and intelligent video analysis technology, it can automatically switch between close-up image to frame speakers and full view image to frame the whole participants, it frees of camera operation during a meeting and enables meeting attendees to focus more on.

Feature

- 1/2.8" Exmor CMOS, 2MP
- 12X optical zoom, up to 72.5°Fov
- Simultaneously output 3G-SDI, HDMI, Ethernet, Up to 1080p60 resolution
- Support H.264/H.265 video compression
- Implemented with both 3D voice positioning technology, body detection and recognition algorithm, it can precisely frame the speakers - Automatically switch between close-up image for speakers and wide angle image for all attendees
- Built-in image switch rules according to actual meeting scenes

Dimension



Technical Specification

Model No.	AMC-G200T
HD Camera	
Image Sensor	1/2.8" CMOS, 2.14MP
Signal Format(SDI)	1080p60/1080p50/1080p30/1080p25/1080i60/1080i50/720p60/720p50
Focal	f=3.9mm-46.8mm
Iris	F1.6-F2.8
Optical Zoom	12x
Digital Zoom	12x
Field of View	72.5 ° - 6.3°
Focus	Auto, Manual, PTZ Push, One Push
Min.Illumination	0.5Lux(Color), 0.1Lux(B/W)
Shutter Speed	1/25 - 1/10,000s
www.winsafecctv.com	
AGC	Auto/Manual
White Balance	Auto, Indoor, Outdoor, One Push, Manual, Auto Track

AE Control Auto, Manual, Shutter Priority, Iris Priority

S/N Above 50dB

DNR 2D/3D

BLC Support

PTZ

Pan Range -90° - +90°

Tilt Range -30° - +90°

Pan Speed 0.1° - +120°/s

Tilt Speed 0.1° - +80°/s

Preset Number 256

OSD Yes

Image Flip Yes

Network

Image Resolution 1920 x 1080 @ 60fps

Video Compression H.264, H.265

Audio Compression AAC

Protocol HTTP, RTSP, RTMP, RTP, TCP, UDP, ONVIF

Dual stream Support

Interface

Video Output 1 x HDMI Interface, 1x 3G-SDI Interface

Audio Input 1 x LINE IN

Audio Output 1 x LINE OUT

Network Interface 1 x 10M/100M

USB Interface 1 x USB2.0

Control Interface 1 x RS-232

General

Control Protocol VISCA/PELCO-P/PELCO-D

Address 0 - 63

Power Supply DC12V

Power Supply Below 50W

Working Temp 0°C - +40°C

Storage Temp -20°C - +60°C

Dimension 500mm x 162mm x 137mm

Weight 3kg