

## USB Lecturer Tracking and Board Writing Detecting System



LTC2-A2001NV2



BLS-200



### System Diagram






### Feature

- ※ USB 2.0 Output
- ※ Precise lock and track capability
- ※ Unmanned and standalone tracking
- ※ Smart tracking performance
- ※ Board writing triggers tracking
- ※ Easy connection, configuration and communication

## Dimension



## Dimension



- ① Audio
- ② TF Card
- ③ Ethernet
- ④ DVI-D
- ⑤ 3G-SDI
- ⑥ RS-232/RS-485
- ⑦ USB 2.0
- ⑧ DC12V


### Accessories for LTC2-A1202

## Technical Data


<b>Model No.</b>	<b>BLS-200</b>
<b>Image Sensor</b>	1/3" Exmor CMOS
<b>Effective Pixel</b>	4.0MP(2560x1440)
<b>Min.illumination</b>	1Lux @ F2.0
<b>S/N Ratio</b>	Above 50dB
<b>Gain</b>	Auto
<b>Shutter Speed</b>	1/30 - 1/10,000s
<b>White Balance</b>	Auto
<b>Focal</b>	2.4mm
<b>View Angle</b>	90°(wide) - 50°(tele)
<b>Aperture</b>	F2.0
<b>Video Compression</b>	H.264
<b>Kbps</b>	32Kbps-8Mbps
<b>Video Frame Rate</b>	720p30, 1080p30
<b>Ethernet</b>	10-100M, Support POE
<b>Power Supply</b>	DC12V, POE
<b>Power Consumption</b>	Below5W
<b>Working Temp</b>	0°C - +40°C
<b>Humidity</b>	Below 90%(No condensation)
<b>Dimension</b>	φ93mm * 81mm
<b>Weight</b>	0.33kg

## Technical Data

<b>Model No.</b>	<b>LTC2-A1202NV2</b>
<b>Tracking Camera</b>	
<b>Image Sensor</b>	1/2.8" Exmor CMOS, 2.14MP
<b>Lens</b>	f=4.7mm-94mm; F1.6-F3.5
<b>Zoom</b>	Optical:20X, Digital:12X
<b>Field of View</b>	59.5° - 2.9°
<b>Focus</b>	Auto, Manual, PTZ Trigger AF, One Push
<b>Mini.illumination</b>	0.5Lux(Color), 0.1Lux(B/W)
<b>Shutter Speed</b>	1/1 - 1/10,000s
<b>Gain</b>	Auto / Manual
<b>White Balance</b>	Auto,Indoor, Outdoor, One Push, Manual, Automatic Tracking
<b>AE Control</b>	Auto, Manual, Shutter Priority, Iris Priority
<b>S/N Ratio</b>	Above 50dB
<b>Full View Camera</b>	
<b>Image Sensor</b>	1/2.8" Exmor CMOS
<b>Effective Pixel</b>	2.15MP
<b>White Balance</b>	Auto
<b>Exposure</b>	Auto
<b>Field of View</b>	Horizontal:86°; Vertical:52°
<b>Lens</b>	2.4mm
<b>PTZ</b>	
<b>Pan/Tilt Angle Range</b>	Pan: -170° - +170° ; Tilt: -30° - +90°
<b>Pan/Tilt Speed</b>	Pan: 0.1° - +120°/s ; Tilt: 0.1° - +90°/s
<b>Preset Number</b>	256
<b>Control Interface</b>	RS232/RS485/USB2.0
<b>Control Protocol</b>	PELCO-D / VISCA / UVC
<b>Network</b>	
<b>Ethernet</b>	RJ45, 100M
<b>Image Resolution</b>	1920x1080 @ 60fps



Wall Bracket



Ceiling Plate

<b>Frame Rate</b>	1080P60/1080P50/1080P30/108025 1080I60/1080I50/720P60/720P50
<b>Video Compression</b>	H.264/H.265
<b>Audio Compression</b>	AAC
<b>Protocol</b>	ONVIF / RTSP / RTMP / TCP / UDP
<b>Dual Stream</b>	Support
<b>Simultaneous Users</b>	Up to 10 users
<b>Video Interface</b>	3G-SDI / DVI-I / USB2.0
<b>General</b>	
<b>Power Supply</b>	DC12V
<b>Power Consumption</b>	<20W
<b>Working Temp</b>	0°C - +40°C
<b>Storage Temp</b>	-20°C - +60°C
<b>Dimension</b>	243mm(L) x 245mm(W) x 163mm(H)
<b>Weight</b>	1.2KG
<b>Color</b>	Grey

\*\*\* Product specification are subject to change without notice \*\*\*