



EVC150 **Point-to-Point** Full HD Video Conferencing System

The EVC150 is video conferencing's price-to-performance leader, offering small to medium-scale organizations a uniquely cost-effective full HD video conferencing solution. The EVC150 features real-time full HD video streaming and HD 720p content sharing along with a PTZ camera, an microphone array, a sleek UI and a compact system design. In addition to its impressive hardware, the EVC150 comes with a 3-year standard warranty and remarkably low total cost of ownership, translating into an astounding return on investment. Whether for point-to-point conferencing, cloud-based video collaboration or hardware system integration, the standards-based EVC150 is the system of choice for savvy VC users.



Full HD video & HD content sharing

Experience natural, real-time video communication on one monitor at HD 1080p 30fps, while sharing presentation files, animation, visualizer images and more on another at HD 720p 30fps, creating a smooth, interactive video conferencing experience.



One-touch recording

Record your video conferences- including video, audio and shared content- directly to a USB flash drive, creating video archives and helping avoid post-meeting information loss. Play back recorded meetings using your EVC150, or on your PC using AVer's VCPlayer software.



PTZ camera with 18X total zoom

The EVC150's powerful full HD PTZ camera offers 12X optical zoom plus 1.5X digital zoom, as well as +/-130° pan and +90°/-25° tilt, quick auto-focus and clear close-ups of participants, making it ideal for any size of conference room.



Connect up to 4 microphones via daisy-chain

The EVC150's all-new microphone array and codec employ an array of sophisticated audio processing technology, such as advanced noise reduction, automatic gain control and echo cancellation, producing crisp, true-to-life sound even better than previous AVer systems.



Remarkable 100 camera presets

No need to waste time panning and zooming manually during EVC150 video conferences – simply program presets on the remote control ahead of time, and during meetings you can shift the camera from a wide view of the room to a close-up of an object with just the press of a button.



Handy integration & remote access tools

Access EVC150 remotely and troubleshoot issues using WebTool, AVer's web-based management platform, and leverage advanced network technology Wake-on-LAN (WOL), Telnet, network test, and HELPeR™ to make the EVC150 the perfect device for integration via LAN or the internet.

Product specifications

Package contents

- Main system unit (codec)
- The New eCam PTZ camera
- EVC microphone array
- IR remote control
- Power supply
- Cables
- Warranty card
- Quick guide

Communications

- H.323, SIP standards, SIP TLS
- 64Kbps~4Mbps
- RJ45 network LAN (10/100/1000)
- Manual bandwidth settings

Camera

- The New eCam PTZ:
 - pan/tilt/zoom camera
 - 2-megapixel CMOS sensor
 - 18X total zoom (12X optical + 1.5X digital zoom)
 - ±130° pan; +90°/-25° tilt
 - 72° FOV (H); 43° FOV (V); 82° FOV (D)

People video resolutions

- HD1080p (1920 x 1080)
- HD720p (1280 x 720)
- 480p (848 x 480)
- 4CIF (704 x 576)
- 4SIF (704 x 480)
- 360p (640 x 360)
- W288p (512 x 288)
- CIF (352 x 288)
- SIF (352 x 240)
- All resolutions at 30fps

Content video resolutions

- Supported resolutions:
 - WSXGA+ (1440 x 900)
 - HD (1360 x 768)
 - SXGA (1280 x 1024)
 - QVGA (1280 x 960)
 - WXGA (1280 x 800)
 - XGA (1024 x 768)
 - SVGA (800 x 600)
 - VGA (640 x 480)

- Output resolutions:
 - HD720p (1280 x 720) up to 30fps

Video standards

- H.264, H.264 HP, H.264 SVC, H.263+, H.263, H.261
- H.239 dual video streams
- BFCP content sharing

Video inputs

- The New eCam PTZ
- VGA

Video outputs

- HDMI
- VGA

Audio standards

- G.711, G.722, G.722.1, G.728, G.722.1C

Audio features

- Automatic gain control (AGC)
- Advanced noise reduction
- Acoustic echo cancellation (AEC)

Audio inputs

- EVC microphone daisy chain up to 4
- Line-in (3.5 mm)

Audio outputs

- HDMI
- Line-out (3.5 mm)

Other supported standards

- H.224, H.225, H.245, H.281, H.323 Annex Q, H.460, SRTP

User interface

- Multiple layout styles
- User-friendly OSD (22 supported languages: English, Traditional Chinese, Simplified Chinese, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazil, Romanian, Russian, Spanish, Swedish, Thai, Turkish)
- Display/edit site name

Network

- 10/100/1000Mbps
- NAT/firewall traversal
- High Efficiency Lost Packet Recovery (HELPeR™)
- API support via Telnet
- Wake-on-LAN (WOL) support
- IPv4 and IPv6 support
- Network Test
- QoS

Security

- AES (Advanced Encryption Standard) function (128-bit)
- Password protection for system settings
- Password protection for remote system management

Web management tool

- Remote management
- Live monitoring
- Firmware update
- Phonebook download/upload/edit
- Restore system settings
- Export call history

Value-added features

- Meeting recording
 - In meeting and offline recording
 - Save directly to USB flash drive
 - Supports screen re-layout during playback
 - Playback and file conversion via VCLPlayer software (.mov/.mp4 format)
- Speed dialing via hot keys (10 sets)
- Camera presets (100 positions)
- Network Time Protocol (NTP)
- ScreenShare
- VCLink
- SnapShot

Power supply

- AC 100V~240V, 50/60Hz
- Consumption: EIAJ 12V, 4A

Environmental data

- Operation temperature: 0~40°C
- Operation humidity: 20%~80%
- Storage temperature: -20~60°C
- Storage humidity: 20%~80%

Physical characteristics

- Package dimensions: 376 x 300 x 243 mm
- Package weight: 6.49kg (14.31lbs)
- Main system (codec): 260 x 158.7 x 33 mm
- The New eCam PTZ: 180 x 144 x 184 mm
- EVC microphone array: 131.9 x 118.6 x 25.5 mm

Warranty

- 3-year standard warranty*

Optional accessories



* For detailed warranty information, please contact an AVer representative.



Edustus ja maahantuonti:

FinnAV Oy MediaSolution
Kantelettarentie 7 R
00420 HELSINKI
Puh.09 - 879 5639
info@mediasolution.fi
www.mediasolution.fi

Hardware specifications

Front panel



Back panel

