

EVC350 4-site MCU Full HD Video Conferencing System

Perfect for any budget, the EVC350 is AVer's affordable, 4-site, high performance MCU video conferencing system. This all-in-one video conferencing solution allows organizations to start conferencing immediately, with no installation fees or costly upgrades. Our patented, intelligent microphones can be linked together to form a daisy chain so you can enjoy great audio reception in any size of conference room. All your important meetings can be recorded directly to a USB fl¬ash drive, even when you are offline. Moreover, you can use the EVC350 with AVer's EZDraw collaborative annotation app to access to an impressive array of interactive tools. Users can also connect to the EVC350 from PCs, laptops, tablets and smart phones via AVer's EZDreetup software. All these great features make the EVC350 the perfect communication solution.great features make the EVC350 the perfect communication.

















License upgrade to 6, 8 or 10 points

EVC350 users can take advantage of our new license upgrade program to expand from up to 4 point communication to up to 10 points. By simply entering the license key you can conveniently upgrade your EVC350 and meet your company's growing communication requirements.

Full HD 1080p video & content sharing

Our EVC350 supports conferencing on up to 4 different sites at full HD 1080p resolution. Its cost-effective embedded MCU offers smooth video streaming along with content sharing, and is the ideal solution for those who want to start video conferencing today.

PTZ camera with 18X total zoom

The EVC350's powerful full HD PTZ camera offers 12X optical zoom plus 1.5X digital zoom, as well as +/-130° pan and +90°/-25° tilt, quick auto-focus and clear close-ups of participants, making it ideal for any size of conference room.

One-touch recording

Record your video conferences- including video, audio and shared content- directly to a USB flash drive, creating video archives that help avoid post-meeting information loss. Play back recorded meetings on your EVC350 or on your PC using AVer's VCPlayer software.

Annotate anytime & anyplace

Using the EVC350 with AVer's EZDraw collaborative annotation app opens up powerful business communication possibilities. Users at different sites can write text, make highlights or draw on the same document, providing an ideal solution for improving the flow of discussions and achieving better mutual understanding.

Connect whenever & wherever you need

The EVC350 can connect up to 4 sites no matter where they are via AVer's EZMeetup mobility software. EZMeetup makes it possible to join video conferences from PCs, laptops, mobile phones and tablets, so all participants can join in important meetings with smooth video and clear audio from nearly any location.



Product specifications

Package contents

- Main system unit (codec)
- The New eCam PTZ camera
- EVC microphone array
- IR remote control
- Power supply
- Cables
- Warranty card
- Quick guide

Communications

- H.323, SIP standards, SIP TLS
- 64Kbps~4Mbps
- RJ45 network LAN (10/100/1000)
- Manual bandwidth settings

Camera

- The New eCam PTZ:
- pan/tilt/zoom camera
- 2-megapixel CMOS sensor
- 18X total zoom
- (12X optical + 1.5X digital zoom)
- ±130° pan; +90°/-25° tilt
- 72° FOV (H); 43° FOV (V); 82° FOV (D)

People video resolutions

- HD1080p (1920 x 1080)
- HD720p (1280 x 720)
- 480p (848 x 480)
- 4CIF (704 x 576)
- CIF (352 x 288)
- SIF (352 x 240)
- All resolutions at 30fps

Content video resolutions

- Supported resolutions:
 HD1080p (1920 x 1080)
- WSXGA+ (1680 x 1050)
- SXGA (1280 x 1024)
- WXGA (1280 x 768) - HD720p (1280 x 720)
- XGA (1024 x 768)
- SVGA (800 x 600)
- D1 (720 x 480)
- VGA (640 x 480)
- Output resolutions:
- HD1080p (1920 x 1080) up to 30fps

USB-1

USB-2

CEFC RoHS

Hardware specifications

power

www.aver.com

Front panel



- H.264, H.264 HP, H.264 SVC, H.263+, H.263, H.261
- H.239 dual video streams
- BFCP content sharing

Video features

3D Denoise

Video inputs

- The New eCam PTZ
- VGA
- DVI (HDMI)

Video outputs

- HDMI
- VGA
- Audio standards
- G.711, G.722, G.722.1, G.728, G.722.1C

Audio features

- Automatic gain control (AGC)
- Advanced noise reduction
- Acoustic echo cancellation (AEC)

Audio inputs

- EVC microphone daisy chain up to 4
- DVI (HDMI)
- Line-in (3.5 mm)

Audio outputs

- HDMI
- Line-out (3.5 mm)

Other supported standards

• H.224, H.225, H.245, H.281, H.323 Annex Q, H.460, SRTP

User interface

Multiple layout styles

- User-friendly OSD (22 supported languages: English, Traditional Chinese, Simplified Chinese, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazil, Romanian, Russian,
- Spanish, Swedish, Thai, Turkish) • Display/edit site name

Network

- 10/100/1000Mbps
- NAT/firewall traversal
- High Efficiency Lost Packet Recovery (HELPeR[™])

MediaSolution

info@mediasolution.fi, www.mediasolution.fi

Environmental data

Operation temperature: 0~40°C

Operation humidity: 20%~80%

• Storage temperature: -20~60°C

Physical characteristics

• Package weight: 6.99kg (15.41lbs)

(free App)

(free App)

• Export .PNG files

Warrantv

3-year standard warranty*

microphone

representative.

audio out

HDMI-1 out

Distributor/Dealer:

Optional accessories

• Package dimensions: 376 x 300 x 243 mm

• Main system (codec): 320 x 262.7 x 37.2 mm

• EVC microphone array: 131.9 x 118.6 x 25.5 mm

Support Windows[®], Mac[®], iOS and Android devices

Mobility software - EZMeetup

• The New eCam PTZ: 180 x 144 x 184 mm

• 30-day free trial for licensed PC version

• Receive resolution up to HD 720p at 30fps

Compatible with firmware later than v10.06

• Support content sharing, capture and recording

Collaborative software - EZDraw

• Compatible with firmware later than v10.12 (BOOM)

camera mount

DC 12V

reset

* For detailed warranty information, please contact an AVer

HDMI-2 out

VGA out

Transmit resolution up to VGA (640x480) at 30fp

Connect with H.264 video coded

Compatible with EVC multipoints

Compatible with EVC multipoints

• Import .JPG, .PNG, .GIF and .BMP files

• A maximum of 10 tablets can be connected

Storage humidity: 20%~80%

Edustus ja maahantuonti:

FinnAV Oy MediaSolution,

Puh.09 - 879 5639

Kantelettarentie 7 R, 00420 HELSINKI

- API support via Telnet
- Wake-on-LAN (WOL) support
- IPv4 and IPv6 support
- Network Test
- QoS

Security

- AES (Advanced Encryption Standard) function (128-bit)
- Password protection for system settings
- Password protection for remote system management

Web management tool

- Remote management
- Live monitoring
- Firmware update
- Phonebook download/upload/edit

Restore system settings Export call history

Value-added features

• Meeting recording

In meeting and offline recording
 Save directly to USB flash drive

• Speed dialing via hot keys (10 sets)

Camera presets (10 positions)

• Network Time Protocol (NTP)

ScreenShare support

VCLink support

Group Calling

SnapShot support

Power supply

• AC 100V~240V, 50/60Hz

Consumption: EIAJ 12V. 4A

Back panel

network

© 2015 AVer Information Inc. All rights reserved. All rights of this object belong to AVer Information Inc. Reproduced or transmitted in any form or by any means without the prior written permission of AVer Information Inc. is prohibited. All information or specifications are subject to change without prior notice. "AVer' is a trademark owned by AVer Information Inc. Other trademarks used herein for description purpose only belong to each of their companies. (201510)

camera in

MIC in

DVI in

0

VGA in

audio in

Find us on Facebook: aver.global, LinkedIn: AVer Video Conferencing and YouTube: AVerInformation

\$

• License upgrade to 6, 8, 10 points

Supports screen re-layout during playback
 Playback and file conversion via VCPlayer software (.mov/.mp4 format)